



**TYPICAL SECTION**  
N.T.S.  
5,000 TO 10,000 AADT

MAX. ALLOWABLE DESIGN SPEED – 45 MPH

1. ALL DIMENSIONS SHOWN ARE MINIMUM.
2. SEE APPROPRIATE SECTIONS OF TECHNICAL MANUAL FOR DESIGN PARAMETERS.
- \*3. PROVIDE 2' MINIMUM CLEARANCE FROM FENCES, WALLS, HEDGES, ABOVEGROUND UTILITIES OR IMPROVEMENTS, DROP OFFS, OR FROM THE TOPS OF BANKS WITH SLOPES STEEPER THAN 1 TO 4, THAT INTERFERE WITH THE SAFE, FUNCTIONAL USE OF THE SIDEWALK. INTERMITTENT ABOVEGROUND UTILITIES, OR MATURE TREES, 2' OR LESS IN DIAMETER MAY BE PLACED IN THIS 2' STRIP AS FAR FROM THE SIDEWALK AS POSSIBLE, IF NOT IN THE CLEAR ZONE.

REVISION DATE :  
04/09

**TRANSPORTATION TECHNICAL  
MANUAL**



**URBAN COLLECTORS  
(2 LANE DIVIDED)  
TYPICAL SECTION**

DRAWING NO. TS-5

SHEET NO. 1 OF 1